

# M-120 PLUS

## MULTI STANDARD PROGRAMMABLE CB MOBILE TRANSCEIVER

### M-120 PLUS MULTI STANDARD PROGRAMMABLE CB MOBILE TRANSCEIVER

State-of-the-art Citizen Band 27MHz mobile transceiver, with advanced hardware and software design, suitable for Citizen Band operators and for car & truck drivers. 9 bands programmable multi standard circuit design, matching the frequency & operating mode requirements of all the European countries. 3-digit LED channel/band indicator, 3W speaker for strong and clear audio sound, fixed or manual Squelch control and Automatic Noise Limiter. New soft type microphone curl cord. Compact sized easy to install cabinet. One radio only, ready for use in all the European countries !

**MULTI STANDARD  
PROGRAMMABLE  
TECHNOLOGY**

**NEW EXTRA SOFT  
MICROPHONE  
CURL CORD**



**9 BANDS**

**3-DIGIT  
LED DISPLAY**

**ANL**

**3W  
SPEAKER**

**SQUELCH +  
AS SQUELCH**

**EMG  
CH9/19**

**QUICK UP  
QUICK DOWN**

**4-PIN MIC  
CONNECTOR**

*feature*  
**PACKED**  
see reverse for full details



**INTEK®**

# M-120 PLUS

## MULTI STANDARD PROGRAMMABLE CB MOBILE TRANSCEIVER

State-of-the-art CB (27 MHz) mobile transceiver,  
with advanced software & hardware design,  
specifically conceived for Citizen Band operators and for truck / car drivers

One radio only, ready for use in all the European countries !

### Main features :

- MULTI STANDARD CIRCUIT DESIGN
- 3-DIGIT BAND / CHANNEL DISPLAY
- 9 BANDS PROGRAMMABLE
- AM / FM
- 3-DIGIT BAND / CHANNEL DISPLAY
- FIXED OR MANUAL SQUELCH
- HIGH QUALITY CONDENSER MICROPHONE WITH 4-PIN RING CONNECTOR
- TX LED INDICATOR
- RX LED INDICATOR
- ANL AUTOMATIC NOISE LIMITER
- QUICK UP / DN CH SELECTION
- EMERGENCY CHANNELS CH9 / CH19
- RUBBER SOFT TOUCH KEYS
- 3W SPEAKER

**NEW EXTRA SOFT  
MICROPHONE  
CURL CORD**

**RoHS**  
2002/95/EC



**MULTI STANDARD  
PROGRAMMABLE  
TECHNOLOGY**

### SPECIFICATIONS

#### GENERAL

Channels	Refer to programmed band
Modes (AM, FM)	Refer to programmed band
Operating Temp.	-10°/+55°C
DC Input Voltage	13.2Vdc ±15%
Size	140(L) x 37(H) x 190(D) mm
Weight	750 gr.

#### RECEIVER

System	CPU Controlled Double Conversion Super Heterodyne
IF	1° 10.695 MHz / 2° 455 KHz
Sensitivity	0.5µV for 20dB SINAD (FM) 0.5µV for 20dB SINAD (AM)
Audio Output Power	@ 10% THD 2.5W at 8 Ohm
Audio Distorsion	<8% at 1 KHz
Image Rejection	65dB
Adjacent Ch. Rejec.	65dB
Signal/Noise Ratio	45dB
Current Drain	350mA (stand-by)

#### TRANSMITTER

System	CPU Controlled PLL Synthesizer
Max Output Power	4W at 13.2Vdc
Modulation	AM (from 85% to 90%) FM (1.8 KHz ±0.2 KHz)
Output Impedanced	50 Ohm unbalanced
Current Drain	1300 mA (at no modulation)

#### FREQUENCY BAND / MODE PROGRAM

E1	ITALY/SPAIN 40CH AM/FM 4W
I2	ITALY 36CH AM / FM 4W
dE	GERMANY 80CH FM 4W / 12CH AM 1W
d2	GERMANY 40CH FM 4W / 12CH AM 1W
EU	EUROPE/France 40CH FM 4W / 40CH AM 1W
CE	CEPT 40CH FM 4W (DEFAULT)
U	ENGLAND 40CH + CEPT 40CH FM 4W
PL	POLAND 40CH AM/FM 4W (-5 KHz)
Pd	POLAND 40CH AM 1W / FM 4W (-5 KHz)

**IMPORTANT !** This 27 MHz CB transceiver has been factory pre-programmed on the CE frequency band (CEPT 40CH FM 4W). This product is subject to national restrictions. Before operating this radio, please check that the frequency band has been correctly programmed according to the country where radio is used. Please read carefully the instruction manual before using this product.



**RECOMMENDED BY INTEK !**

**LEADER IN CB 27 MHz  
CAR & TRUCK MOBILE ANTENNA**

**RECOMMENDED BY INTEK !**



**LEADER IN CB 27 MHz  
CAR & TRUCK MOBILE ANTENNA**



CE 0678 ! CH



**INTEK®**